

NO FLAT ROOFS ALLOWED. You can run a stock fiberglass replacement, example:
Speedway.com part number 910-54177

4. No open holes in firewall or stock floor pan and MUST have firewall between driver and trunk
5. Enclosed cockpits are allowed but MUST have an inspection hole
6. Rear of car must be closed in
7. Aftermarket nose and tail piece are allowed
8. Fabricated bumpers are allowed
9. The rear of the car must have 2 inches of downward slope from the rear glass area to the edge of the trunk lid or tail piece. A minimum of 2 inches.
10. NO SPOILERS ARE ALLOWED
11. You can run STOCK floor pan and firewalls in stock location
OR
 - a. Minimum of three windshield bars in front of driver.
 - b. Aluminum high-back seat only, must be bolted in using minimum 0.375 inch bolts. Seat must remain inside all confines of roll cage. Maximum 70 inches from the back of the engine block to the front side of seat, measured at the shoulder harnesses.
 - c. Driver must be sealed off from track, driveline, engine and fuel cell.
 - d. Kick and rocker panels may be removed.
 - e. Front OEM firewall may be replaced using steel fabricated full firewall, 18 gauge or minimum 0.049-inch thickness. Entire firewall can be no further back than 12 inches from the back of engine block, measured horizontally.
 - f. Dash must not extend more than 24 inches back from top of firewall. Dash must be flat, extend from door to door, rear can be no higher than front, except for cowl in front of driver.
 - g. OEM floor pan may be replaced using steel fabricated floor pan, 18 gauge or minimum 0.049-inch thickness, securely welded to frame. Floor pan may be replaced from front firewall to rear halo supports. Must remain flat/OEM appearing from frame rail to frame rail, can be no higher or lower than frame rail. Exception is maximum eight-inch-tall driveshaft tunnel. Tunnel must remain similar to OEM tunnel in size.
 - h. All holes in firewalls must be covered with metal.
 - i. No driver adjustable devices allowed while car is in competition except brake adjuster.
 - j. No mirrors.

Wheels & Tires:

1. 15 x 8 steel wheels only
2. 5 lugs minimum,
3. No wide 5
4. Bead locks right side only
5. Mud Covers are Okay
6. Any DOT Street tire or Hoosier H500 or American Racer AR500 or ARstocker, G60 Stocker Hard are allowed
7. Grooving or siping is allowed.
8. No mud grips

Safety:

1. MUST have working fire extinguisher mounted within reach of the driver
2. Full driver's suit and helmet with shield are MANDATORY
3. Racing seat and belts will be no older than three (3) years from date of manufacturer

ANYTHING THAT IS NOT COVERED IN THE RULES WILL BE DECLARED LEGAL OR ILLEGAL BY THE OFFICIALS